



# Granito Impregnator™

## TECHNICAL DATA SHEET

### PRODUCT BENEFITS

EcoStone Solutions Granito Impregnator is a premium impregnating, natural look, water based treatment for granite to provide maximum stain protection. Allows vapor transmission. Also used as a grout sealer.

### RECOMMENDED SURFACES

For use on:

- Granite Limestone
- Slate Sandstone
- Clay Products Grout

Suitable also for:

- Travertine Marble

### Available Sizes

Quarts, Gallons, 5 gallon pails, 55 gallon drums

### Coverage

300-1500 SF (30-139 Sq meters) per coat per gallon depending on the porosity and texture of the material, method of application, humidity, and surface temperature.

### Directions

- Always test in an inconspicuous area before general use.
  - Make sure surface is clean, vacuuming or sweeping off all debris.
  - Mask off and protect areas such as baseboards or adjacent surfaces not intended for treatment.
  - Make sure surface is clean and dry prior to application.
  - EcoStone Solutions Granito Impregnator may be applied to damp surfaces one hour after moisture has been removed.
  - Apply an even coat using a paint pad, paint brush, paint roller, or low-pressure sprayer delivering a coarse wet spray.
  - Allow penetration for 10-15 minutes, then wipe off all remaining product immediately.
  - A full cure can be expected in 48-72 hours. Foot traffic can begin after 4 hours.
  - Reapply Granito Impregnator as needed for periodic maintenance. This will depend on traffic patterns, sun exposure, maintenance procedures, etc.
- 
- No chlorinated solvents
  - No petroleum distillates
  - VOC compliant in all states
  - Environmentally responsible
  - Easy to use and low odor
- 
- Excellent protection against the toughest oil and water-based stains
  - This product may help you achieve LEED certification



For more information on this product and other products for tile and stone care please visit your distributor or our website at [www.ecostonesolutions.com](http://www.ecostonesolutions.com)